CLAIMS

What is claimed is:

7.

1

1	1.	A weapon for use by an operator, the weapon comprising:	
2		apparatus that provides lethal force, non-lethal force, and illumination;	
3		a first trigger operable with a first hand of the operator for releasing the lethal force; and	
1		a switch and a second trigger, the switch operable with a second hand of the operator	
5	when the second hand is in a position to operate the second trigger, the second trigger for releasing		
5	the non-lethal force; wherein		
7		the illumination is controlled in response to operation of the switch.	
l	2.	The weapon of claim 1 wherein the illumination is for aiming the non-lethal force.	
l	3.	The weapon of claim 1 wherein the non-lethal force comprises electromuscular stimulation.	
l	4.	A weapon comprising:	
2		apparatus that provides lethal force and non-lethal force;	
3		a circuit comprising a switch and a source of illumination, wherein:	
1		(1) the circuit controls illumination from the source for aiming the non-lethal force;	
5	and		
6		(2) the circuit controls release of the non-lethal force in response to operation of the	
7	switch.		
l	5.	The weapon of claim 1 wherein the non-lethal force comprises electromuscular stimulation.	
l	6.	A support for attaching an implement to a firearm, the firearm having a rail and a stop, the	
2	support comprising:		
3		means for mechanically coupling the implement to the rail; and	
ļ		means for coupling the implement to the stop to reduce motion of the implement along	
5	the ra	the rail parallel to a direction of delivery of the lethal force.	

The support of claim 6 wherein the rail conforms to a picatinny rail.

- 1 8. The support of claim 6 wherein the stop comprises a sight.
- 9. A support for attaching a non-lethal implement to a firearm, the firearm having a rail and a
- 2 stop, the support comprising:
- a first channel that receives the rail to mechanically couple the non-lethal implement
- 4 and the rail;
- 5 a first abutment surface that abuts the stop;
- a first fastener that maintains the first abutment surface against the stop;
- 7 a second channel that receives the non-lethal implement; and
- 8 a second fastener that retains the non-lethal implement in the second channel.
- 1 10. The weapon of claim 9 wherein the implement delivers a non-lethal force comprising
- 2 electromuscular stimulation.
- 1 11. The support of claim 9 wherein the rail conforms to a picatinny rail.
- 1 12. The support of claim 9 wherein at least one of the first fastener and the second fastener is
- 2 manually releasable without a tool.
- 1 13. The support of claim 12 wherein the at least one fastener is released by manually
- 2 accomplishing a rotary motion of a portion of the fastener to an extent less than 720 degrees.
- 1 14. The support of claim 9 wherein the implement delivers non-lethal force from the front of
- 2 the implement and the second channel comprises a second abutment surface that faces a rear
- 3 surface of the implement.
- 1 15. The support of claim 9 wherein:
- 2 the support comprises a first portion and a second portion; and
- 3 the first fastener mechanically joins the first portion of the support to the second portion
- 4 of the support.

- 1 16. The support of claim 9 wherein:
- 2 the support comprises a first portion and a second portion; and
- 3 the second fastener mechanically joins the first portion of the support to the second
- 4 portion of the support.
- 1 17. The support of claim 9 wherein:
- 2 the support comprises a first portion retained to the rail and a second portion retained to
- 3 the implement; and
- 4 the support further comprises means for separating the first portion from the second
- 5 portion without operation of the first fastener or the second fastener.